

DOOR CLOSERS SERIES 2000

HIGH PERFORMANCES FOR SUPERIOR DOOR CONTROLS



SMOOTH OPENING, STRONG CLOSING





With series 2000, MAB adds new closing solutions to the existing wide range. Art. 2240

with regular arm satisfies the most demanding needs for a total quality closer.

Tested to 2 milion cycles according to American Standards ANSI156.4.

Design, smooth opening & strong closing, abuse resistance are the main innovative characteristics.

FEATURES


- Adjustable power 1- 6 EN1154
- Vertical adjustability of arm
- Two speed valves
- Adjustable hydraulic Back Check
- Adjustable Delayed Action (option)
- Two overpressure relief valves
- Insensitive to temperature changes betwen –35° and +50° C

- High efficiency
- Suitable for fire doors
- Regular or reversed mounting.
- Full body covers in: ABS, polished brass, satin s/steel
- Finishes for ABS covers : silver, gold, black, bronze, white
- Suitable for interior or exterior doors
- Suitable for doors up to 1400 x 2500 mm


ADJUSTMENTS

Vertical adjustment of arm:

the height of the arm can be adjusted up to 14 mm by moving upwards the grooved pinion.




Adjustment of closing power, of closing speeds, of Back Check, of Delayed Action




ACCESSORIES

MOUNTING PLATES

AC 328 angle bracket



AC 329 DIN back plate



COVERS



CLOSING FORCE CHARTS

EN 1154 (European Standards)

Door closer size	Closing torque Nm (0°-4°) min.	Recommended door leaf width mm max.	Door leaf mass kg.
1	9	750	20
2	13	850	40
3	18	950	60
4	26	1100	80
5	37	1250	100
6	54	1400	120
7	87	1600	160

ANSI 156.4 (American Std.)

_					
	Door closer size	Closing torque Nm (0°-4°) min.			
l					
ı	2	10			
	3	17			
ı	4	27			
	5	37			
ı	6	47			

MAB

MAB S.p.A.

Via del Tuscolano, 6 40128 BOLOGNA (ITALY) Tel. +39.051321567 Fax. +39.051325108

E-mail: mab@mab-spa.com www.mab-spa.com